

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-288130

(43)Date of publication of application : 31.10.1995

(51)Int.Cl. H01M 4/40
H01M 4/02
H01M 10/40

(21)Application number : 07-034126 (71)Applicant : MITSUBISHI CABLE IND LTD
(22)Date of filing : 22.02.1995 (72)Inventor : TAKADA YOSHINORI
SASAKI KOZO
MARUMOTO MITSUHIRO

(30)Priority

Priority number : 06 49869 Priority date : 22.02.1994 Priority country : JP

(54) NEGATIVE ELECTRODE ALLOY FOR LITHIUM SECONDARY BATTERY AND LITHIUM SECONDARY BATTERY

(57)Abstract:

PURPOSE: To enhance electromotive force, charging/discharging capacity, energy density, and lengthen charging/discharging cycle life by using a Li-Ag-Te system alloy having a specified composition range in a negative electrode.

CONSTITUTION: The composition of a negative electrode alloy is preferably represented by formulas I, II, and III. By the γ_1 phase of a Li-Ag system alloy, which relates to absorption/desorption of lithium, of a Li-Ag-Te system alloy, discharging capacity is maintained for a long time and charging/discharging cycle life is lengthened. By an intermetallic compound such as Ag₂Te and Li₂Te, crystal grains are made fine, diffusion of lithium and silver is accelerated, absorption/desorption

Li:Ag:Te=15~130:1~20:0.501~2

I

Li:Ag:Te=80~150:1~20:0.901~24/5

II

Li:Ag:Te=10~120:1~20:0.901~5

III

Li:Ag:Te:M:V2=15~120:1~20:0.901~24/5
0.901~24/5~50:1~80

IV

efficiency of lithium is enhanced. By containing M1-M2 system alloy composition represented by formula IV, deterioration of negative electrode attendant on absorption/desorption of lithium is retarded by the binding effect of this intermetallic compound. Alloying is made by conventional melting process or vapor deposition process. (In formula IV, M1 is a 3B-5B group metal, and M2 is a transition metal excluding Ag).

LEGAL STATUS

[Date of request for examination] 04.03.1997

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 2968447

[Date of registration] 20.08.1999

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right] 20.08.2002

Copyright (C); 1998,2003 Japan Patent Office